INSTALLATION GUIDE AGTIV[®] Liquid Injection Kit

Premier Tech Agriculture recommends a customized equipment, such as the Dosatron[®] Injection System, for the application of its liquid inoculants. Designed for an easy application of AGTIV[®] liquid products, the AGTIV[®] Liquid Injection Kit operates off the main solution flow of existing in-furrow application system.

The installation of the AGTIV® Liquid Injection Kit requires two steps:



INSTALL THE INJECTION KIT ON THE EXISTING IN-FURROW SYSTEM

Version française du guide d'installation disponible sur PT**AGTIV**.COM

PREPARE THE INJECTION KIT

1.1

Have all the required parts for the installation

AGTIV

2

PTAGTIV.

The box will contain the following parts:

- **1** Dosatron[®] pump with all fittings (1x)
- 2 Tank on a metal stand (1x)
- 3 Reducing nipples (4x)
- 4 Hose clamps (4x)
- 5 Grey bracket with large hose clamp (1x)
- 6 Coupler (1x)
- 7 Stainless steel shaft (1x)
- 8 Mixing impellers (2x)
- 9 12-Volt motor and wire (1x)
- 10 Basket screen for the tank (1x)





INSTALLATION GUIDE

NOTE: Purchase the following parts to install the AGTIV[®] Liquid Injection Kit on the existing in-furrow system:

- Teflon
- Hose (size depends on your equipment)
- Hose clamps (2x)
- Parts to build a bracket (see 2.2-a on page 3)





IMPORTANT

The installation of the AGTIV[®] Liquid Injection Kit **requires approval** by a Premier Tech Agriculture **representative**. In this regard, pictures of the installation must be sent before usage to Premier Tech Agriculture at the following email address: **info@ptagtiv.com**.

1.2 Assemble the AGTIV[®] Liquid Injection Kit following these steps:







d Fix the suction hose of the Dosatron® to the valve under the tank. Cut the length of the suction hose (if necessary) to eliminate any loop in the hose (this will prevent the stagnation of the liquid).





Select the right reducing nipple size to connect the **Main flow hose 1** from the existing in-furrow system to the AGTIV[®] Liquid Injection Kit & to the outlet **2**.

f



2 INSTALL THE INJECTION KIT ON THE EXISTING IN-FURROW SYSTEM

See below a diagram of where the AGTIV[®] Liquid Injection Kit should be integrated on the existing in-furrow system.



Select where to install the equipment on the planter/seeder



These are recommendations to ensure the good performance of the equipment:

- Solution Prevent damage by other parts of the equipment
- Make sure the suction hose of the Dosatron[®] unit is visible
- Have an easy way to fill, empty, clean and maintain the tank
- Install where the dust is minimum

2 Install the AGTIV[®] Liquid Injection Kit on the planter/seeder





Install the AGTIV® Liquid Injection Kit on the planter/seeder (cont'd)

Measure the length of the **hoses** between the Dosatron[®] unit and the flow divider unit С of the existing in-furrow system. Tie the hoses together to make sure е they will not move.

If desired: add a 2-way switch to be able to turn

the mixer off and on, install a 12-volt electrical wire from the tractor to the electrical motor of the mixer. Make sure that the motor runs at all times when using the AGTIV® Liquid Injection kit.

> On the planter, remove all cylinder screens by the nozzles.



Before using the AGTIV[®] Liquid Injection kit, send pictures of the installation at info@ptagtiv.com

CONTACT OUR DEDICATED TEAM TODAY. WE CARE ABOUT YOUR SUCCESS!



f

g

h

PTAGTIV.COM

1866454-5867 info@ptagtiv.com

(f) (in) 🖸 😏

The information in this document was up-to-date at the time of printing. Because of its continuous improvement policy, Premier Tech Agriculture reserves the right to halt manufacturing, change products, or revise technical data and prices without further warning or liability. © Premier Tech Ltd., 2019





INSTALLATION GUIDE